

09786837.080601
TD9080.75898760

21. The new claims conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

The amendments to the specification and abstract reflected in the substitute specification are to conform the specification and abstract to U.S. Patent and Trademark Office rules, and do not introduce new matter into the application.

The underlying PCT Application No. PCT/EP00/05367 includes an International Search Report, Issued October 6, 2000, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

Applicants assert that the present invention is new, non-obvious, and useful. Prompt consideration and allowance of the claims are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

Dated: 3/9/01

By: *[Signature]*
By: *[Signature]*
Richard L. Mayer
Reg. No. 22,490

One Broadway
New York, NY 10004
(212) 425-7200
(212) 425-5288

356318

METHOD AND DEVICE FOR FORMING
THE INTENSITY PROFILE OF A LASER BEAM

[Technical]
Field of the Invention

09786837-080601
The present invention relates to a method and a device
for forming the intensity profile of a laser beam, in
5 particular for producing a homogeneous intensity profile,
as well as to the use of an optically addressable spatial
light modulator (OASLM) for forming the intensity profile
of a laser beam.

10 Background of the Invention

The physical properties of laser light differ
fundamentally from those of conventional light sources.
Laser light is coherent and can be produced as a light
15 beam having a small, even if finite aperture angle. This
narrow beam concentration is particularly advantageous
for illumination and imaging purposes, since the wave
fronts of the laser light approach the ideal of plane
waves. They [are very easily] can be transformed into
20 spherical wave fronts and can be utilized for highly
resolving, diffraction-limiting focusing.

One drawback of the laser beam is its Gaussian character,
which is determined by the manner in which light is
25 generated in the resonator. The intensity distribution of
the light transversely to the beam has the shape of a
Gaussian bell curve. This means that the intensity is at
a maximum in the middle of the beam, and it then drops
off exponentially toward the edges.

30

2L302703314

-1-

MARKED UP VERSION OF SPECIFICATION

09786837.080601
109080 2288760

5 This is [particularly disadvantageous] a drawback in image
processing and projection technologies which require
illuminating flat photomasks. However, it is also a
drawback in interferometry, where one desires a most
uniform possible illumination of the lighted surface[is
critical]. Such uniformity is not provided when working
with a Gaussian intensity profile. In material processing
as well, such as in medical applications involving
heating of tissue, or in laser welding, uniform heating
10 is required over the entire width of the laser beam or of
the illuminated surface. Such uniform heating cannot be
attained when working with a Gaussian shaped illumination
and, thus, for instance, a Gaussian energy deposition.
For that reason, the cross-sectional profile of the light
15 beam should be as rectangular as possible for the areas
of application mentioned. The spatial intensity profile
should be homogeneous, i.e., more or less constant over a
certain width. To effect this, in practice, the beam is
widened and one then works only with the more or less
20 homogeneous[,] inner beam region[,] with the outer region
being masked out. However, this can lead[s] to
significant intensity losses.

25 Since the actual laser system, the optical amplification
medium in the resonator, is not readily accessible to the
user, the forming of the beam into a rectangular profile
must take place outside of the laser. For this purpose,
optical filters, so-called "bull's eye" filters are
known, which attenuate the laser beam more vigorously in
30 the middle than at the edges, thereby flattening the bell
shape of the beam profile to a virtually rectangular
profile. For the most part, these filters are made of a
transparent plate, e.g., a glass plate, upon which a more
or less reflective coating, for example a metal, is
35 coated by vapor deposition. The desired beam profile is

00786837-080604

produced by properly selecting the locally dependent optical density, i.e., the local transmission and reflection properties. These filters are static and, therefore, can only be used for a specific laser having a fixed, known intensity profile. When the laser changes its profile, e.g., due to fluctuations or manifestations of aging, the filters undesirably alter the shape of the profile, since they are no longer adapted to the laser data. Another disadvantage associated with reflecting filters of this kind is that unevenly reflected laser light has a reactive effect on the laser and can degrade its stability. Moreover, in place of reflecting filters, it is also generally known to use holographic filters for forming beams[()]. See, for example, I. Gur et al.: Diffraction limited domain flat-top generator; Opt. Communications 145, 237 (1998)[()], incorporated herein by reference. These filters are also static and are not responsive to time-related changes in the laser beam profile. Also problematic is the fact that the rectangular profile is only produced in the imaging plane of the holographic element.

[Technical Objective

The underlying objective] Summary of the Invention

The present invention [is, therefore, to form] provides a device and method for forming the most homogeneous possible, rectangular beam profile from any initial intensity profile[at all, in particular from]. The present invention further provides a device and method for forming the most homogeneous possible, rectangular beam profile for a Gaussian beam profile, [the intention being for] so that, among other things, the formed beam profile [to] can be substantially stable with respect to

fluctuations in the incident intensity profile and in the light intensity.

[

Detailed Description of the Invention

5

The objective is achieved by a method] The present invention further provides a method for forming the intensity profile of a laser beam, in particular for producing a homogeneous intensity profile, the laser beam

10

[] striking an optically addressable spatial light modular (OASLM), whose local transmission or reflection properties depend in nonlinear fashion on the local illumination intensity.

15

[A device in accordance with] An embodiment of the present invention provides a device for forming the intensity profile of a laser beam, in particular for producing a

20

homogeneous intensity profile, is composed of an optically addressable spatial light modular (OASLM), whose local transmission or reflection properties depend in nonlinear fashion on the local illumination intensity, as well as of at least one telescope imaging system, which is capable of spatially widening the laser beam.

25

[Furthermore, the objective is achieved by the use of] Some embodiments of the present invention further

30

provide using an optically addressable spatial light modular (OASLM) for forming the intensity profile of a laser beam, in particular for producing a homogeneous intensity profile.

35

[T] Some embodiments of the present invention further provide[s] a beam former, i.e., a method for forming beams, where the formed intensity profile is stabilized with respect to changes in the original intensity profile

through the use of an active or adaptive optical element having optical properties that are dependent upon the local illumination intensity. [In particular, a]An optical element [is]can be used[,] whose local transparency changes with the local illumination intensity. A defined beam profile, which is virtually independent of fluctuations in the initial intensity distribution, is automatically produced. [In principle, t]This [is]can also be done without any additional controlling external influence. For that reason, the method and the beam former, respectively, can be used for any laser systems at all, and only need to be adapted to a minor degree to prevailing conditions.

[In accordance with]An embodiment of the present invention[,] further provides that the optically non-linear element is an optically addressable spatial light modulator (OASLM) or a liquid crystal light valve. [It is preferably]The optically non-linear element can be driven in the saturation range to produce a homogeneous (rectangular) laser beam profile; the locally transmitted intensity [is]can then independent of the local illumination intensity.

Optically addressable spatial light modulators (OASLM) are known, for example, from "Spatial Light Modulators; OSA - Technical Digest ISBN 155752-494-7 Washington 1997["], hereby incorporated by reference herein, which are made of a photoconductive layer and of an electro-optical, voltage-sensitive layer. In response to local irradiation, the voltage in the photoconductor breaks down locally and is transferred to the electro-optical layer. On a localized basis, this alters the transmission or reflection characteristics of the electro-optical layer, which, in turn, is now optically indicative of the

09786837.080601
irradiation. The photoconductive layer must be sensitive to the wavelength of the incident light. The electro-optical layer is, for example, a liquid crystal, which has optical modulator properties within broad spectral ranges. Certain materials unite the properties of the photo-sensitive and voltage-sensitive layer, such as photorefractive crystals or polymers (Spatial Light Modulators; OSA - Technical Digest ISBN 155752-494-7 Washington 1997, M. Petrov et al.: Photorefractive Crystals, Berlin 1991).

[In accordance with t]The present invention[,] provides liquid crystals which can have nonlinear optical properties [are] and can be used in OASLMs. [T] In the present invention, the OASLM [is] can be based, for example, on nematic or helical smectic liquid crystals, the latter having an operating frequency of 10^2 to 10^3 Hz, thereby facilitating faster reactions to output profile changes than do elements based on nematic liquid crystals (switching times in the range of 10^{-2} s). The modulation properties of these liquid crystals depend nonlinearly on the applied voltage and, thus, on the local illumination intensity 1 on the photoconductor.

[A typical] In the present invention, a transmission characteristic of an OASLM of this kind [is] may be exemplified by a linear relation between the illumination intensity and transmitted intensity for low illumination intensities, as well as by a transition into the saturation range, where the transmitted intensity is virtually independent of the illumination intensity. For higher intensities, the transmitted intensity can again depend more heavily on the illumination intensity.

The [above described]properties of [an] the OASLM in the

09786837.080601
109080.75898760

present invention can thus enable[, in particular,] high
light intensities to be attenuated more vigorously than
low intensities. In this manner, the intensity of a
Gaussian beam in the center [is] can be suppressed as
5 compared to the edge regions, and the transmitted
intensity approaches a rectangular shape having a flat
plateau in the center.

[One advantageous further refinement] Another embodiment
10 of the present invention provides [for] that the OASLM
layers[to] undergo pattern delineation[, preferably]. A
further embodiment provides that the OASLM layers are
resolved into individual zones, in particular optical
points (pixels), [preferably] and in a possible embodiment
15 of the present invention, can be capable of being driven
individually. This diminishes crosstalk between nearby
picture elements. [Finally, t] This permits electrical
intervention in the modulator, on a pixel-by-pixel basis,
in particular an adaptation of the local transmission
20 properties, targeted to the initial intensity profile.
One can[advantageously] regulate the driving of the
individual zones by measuring the shaped beam profile and
examining it for deviations from a nominal form, in
particular from the rectangular form. By way of a
25 feedback path, the magnitude of the local deviations is
then used as a basis for adapting the transmission
properties of the zones or of the picture elements of the
OASLM.

30 [T] In some embodiments of the present invention, to work
in the saturation region of the OASLM, the intensity of
the laser beam to be shaped [is] can be preferably adapted
by widening the beam and/or through the use of optical
filters at the saturation region of the OASLM. For
35 purposes of beam widening, an optical imaging system

09786837-080601

[is] can be preferably inserted into the optical path of rays, within which the OASLM is located. The optical imaging system [preferably] can encompass two telescope imaging systems, preferably designed as mechanically or electrically adjustable or controllable zoom systems. Thus, the beam widening [is] can be variable, so that changes in intensity can always be compensated by intensity fluctuations of the laser or by replacing the laser.

Brief [d]Description of the [drawing, illustrating:] Drawings

Figure 1[] shows a typical transmission characteristic of an OASLM[
Figure 2 three set-ups according to] in accordance with the present invention;
Figure 2a shows an embodiment of the present invention for forming a beam with the use of an OASLM;
Figure 2b shows another embodiment of the present invention for forming a beam with the use of an OASLM; and
Figure 2c shows another embodiment of the present invention for forming a beam, with the use of an OASLM.

Detailed Description

Figure 1 schematically depicts a typical transmission characteristic of an OASLM, as used in accordance with the present invention, the incident intensity being plotted on the x-axis and the transmitted intensity on the y-axis. For low intensities, the OASLM has a substantially linear transmission characteristic, for

example, it is essentially transparent to the incident radiation. For higher incident intensities, the transmitted intensity is substantially independent of the incident intensity; this saturation range is selected as the working range for the beam formation. The intensity of the incident laser beam to be formed [is] can be adapted to this working range by filters or by widening the beam. In this context, [the advantage of] by widening the beam [is that], once it has passed through the OASLM, the light is able to be focused again[, so that] and there is minimal loss of total intensity.

Three set-ups are shown in Figures 2a-c for forming a beam in accordance with the present invention, using an OASLM. Figure 2a illustrates a set-up where the OASLM is inserted between two coupler telescopes 1, 2, into the laser's path of rays. Telescopes 1, 2 each include two lenses having focal lengths f_1 , f_2 and f_1' , f_2' , respectively, arranged at a distance of f_1+f_2 and $f_1'+f_2'$, respectively. The telescopes [are] can be used for beam widening, to reduce the intensity in the laser beam center to the point where it coincides with the plateau region of the characteristic in accordance with Figure 1. The laser beam having the flattened beam profile exits the second telescope 2 to the right. If it is necessary to simultaneously widen the beam, the right telescope 2 must have a smaller magnification than the left telescope 1.

In certain cases, for example, once a laser is coupled into an optical fiber, the laser intensity can already be optimally adapted to the OASLM. Without any previous widening, the light can then be directly conducted to the OASLM, as shown in Figure 2b. The light from fiber 3 then falls directly on beam former OASLM, which can be in

optical contact with fiber 3. Reflection losses experienced during the transition into the OASLM, are able to be kept to a minimum in this case by using an oil to adapt the refraction index. [The advantage of this specific embodiment is that] Thus the OASLM can have an especially small type of construction in this embodiment of the present invention.

When [one is experiencing]heavy fluctuations in laser intensity is being experienced, or when the intention is to use the same beam former for different types of lasers, it is recommended to connect two zoom telescopes 5, 6 instead of telescopes having fixed magnifications, as in Figure 2a. [T]A possible embodiment of this is shown schematically in Figure 2c. In this case, the beam widening can be altered and, given electrically adjustable zoom telescopes, also controlled.

[Industrial Applicability

]The present invention has many diverse industrial applications. [In particular, it is advantageously]The present invention can be employed in applications where the most uniform possible illumination of surfaces by laser light is critical, especially when working with image processing and projection technology, in interferometry, as well as in material processing where the use of lasers is required.

[
]

[
]Abstract

The present invention relates to a method and a device
5 for forming the intensity profile of a laser beam, in
particular for producing a homogeneous intensity profile.
In an embodiment of the present invention, the laser beam
[striking] can strike an optically addressable spatial
light modular (OASLM), whose local transmission or
10 reflection properties depend in nonlinear fashion on the
local illumination intensity. [By using an OASLM of this
kind, a beam former is created, which, in principle,
without any additional external influence, automatically
generates a virtually rectangular beam profile, which is
15 independent of fluctuations in the initial intensity
distribution and is suited for use in any laser system at
all.]

109080" 2E898760